

MLS 125 STATIC REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Static Refrigeration System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 8°C
	125 L
	595w x 595d x 840h

+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

MLS 125 STATIC REFRIGERATOR

NULINE
REFRIGERATION

MODEL	MLS125
Gross Capacity	125 L
External Dimensions in mm (w/d/h including castors or legs)	595 x 595 x 840
Internal Dimensions in mm (w/d/h)	510 x 410 x 680
Packed Dimensions in mm (w/d/h including pallet)	695 x 595 x 970
Gross Weight – kg (packed weight)	55
Net Weight – kg	42
Voltage	240V
Temperature Range	2°C to 8°C
Ambient Temperature Range	10°C to 32°C
Refrigerant	R134a
Cooling System / Defrost	Static / Manual
Exterior Cabinet Finish	White Enamel
Inner Liner Material	White Enamel
Door	Solid / Glass
Door Hinge	RH
Door Handle	Pull Handle
Type of Controller	Digital
Temperature Display	External
Data Logger	Yes
Door Ajar Alarms	Yes
High and Low Readout	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Yes Optional
Port Entry	Yes
Battery Back-Up for Controller	Yes
Power Requirement	10amp GPO
Castors	No
Adjustable Shelves	3
Usable Shelf Area in mm (w/d)	3 x 495x405 & 1 x 495x260

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au

Nuline Refrigeration reserves the right to alter the specifications without prior notice.



Global-Mark.com.au®

NOVEMBER 2022