

NHR PHARMACY REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Bottom Mounted System
- E-Glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Door Lock
- Interior Lighting
- Door Lock on Handle
- Available in Solid or Glass Doors
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 8°C
	350 L 590 L
	600w x 620d x 1915h 770w x 750d x 1965h



+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

NHR PHARMACY REFRIGERATOR

NULINE
REFRIGERATION

MODEL	NHR400	NHR600
Gross Capacity	350 L	590 L
External Dimensions in mm (w/d/h including castors or legs)	600 x 620 x 1915	770 x 750 x 1965
Internal Dimensions in mm (w/d/h)	440 x 570 x 1435	670 x 600 x 1530
Packed dimensions in mm (w/d/h including pallet)	650 x 670 x 2060	820 x 800 x 2115
Gross Weight – kg (packed weight)	101	123
Net Weight – kg	95	115
Voltage	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	White Colourbond	White Colourbond
Door	Solid / Glass	Solid / Glass
Door Hinge	RH	RH
Door Handle	Full Length	Full Length
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirements	10amp GPO	10amp GPO
Watts	480W	575W
Castors	Yes	Yes
Adjustable Shelves	6	6
Usable Shelf Area in mm (w/d)	480 x 450	650 x 580
Light	LED	LED

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHRS SPARK SAFE REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Bottom Mounted System
- E-Glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Glass or Solid Door
- Auto Water Disposal
- Castors
- Door lock
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 8°C
	350 L 590 L
	600w x 620d x 1915h 770w x 750d x 1965h



+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

NHRS SPARK SAFE REFRIGERATOR



MODEL	NHRS400	NHRS600
Gross Capacity	350 L	590 L
External Dimensions in mm (w/d/h including castors or legs)	600 x 620 x 1915	770 x 750 x 1965
Internal Dimensions in mm (w/d/h)	500 x 470 x 1750	670 x 600 x 1800
Packed Dimensions in mm (w/d/h including pallet)	700 x 720 x 2065	870 x 850 x 2115
Gross Weight – kg (packed weight)	102	121
Net Weight – kg	95	112
Voltage	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Static / Auto	Static / Auto
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	White Colourbond	White Colourbond
Door	Solid / Glass E-Glass	Solid / Glass E-Glass
Door Hinge	RH	RH
Door Handle	Lockable	Lockable
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Castors	Yes	Yes
Adjustable Shelves	5	5
Usable Shelf Area in mm (w/d)	480 x 450	650 x 580

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHRTS TOP MOUNTED SPARK SAFE REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Bottom Mounted System
- E-Glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Door Lock
- Interior Lighting
- Door Lock on Handle
- Available in Solid or Glass Doors
- Digital Display with Built-in Alarms
- Hi/Lo Readout



2°C to 8°C



350 L
590 L



600w x 620d x 1980h
770w x 750d x 2030h



+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

NHRTS TOP MOUNTED SPARK SAFE REFRIGERATOR

NULINE
REFRIGERATION

MODEL	NHRTS400	NHRTS600
Gross Capacity	350 L	590 L
External Dimensions in mm (w/d/h including castors or legs)	600 x 620 x 1980	770 x 750 x 2030
Internal Dimensions in mm (w/d/h)	440 x 570 x 1435	670 x 600 x 1500
Packed Dimensions in mm (w/d/h including pallet)	650 x 570 x 2130	820 x 800 x 2180
Gross Weight – kg (packed weight)	102	122
Net Weight – kg	95	115
Voltage	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Static	Static
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	White Colourbond	White Colourbond
Door	Solid / Glass E-Glass	Solid / Glass E-Glass
Door Hinge	RH	RH
Door Handle	Lockable	Lockable
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Watts	386W	480W
Castors	Yes	Yes
Adjustable Shelves	5	5
Usable Shelf Area in mm (w/d)	480 x 450	650 x 580

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHF SPARK SAFE FREEZER

NULINE
REFRIGERATION

The NHF Spark Safe Freezer for Medical and Laboratory is the smartest, economical and safety way to store your products.

This Freezer is proudly manufactured in Australia, providing the quality and reliability required.

FEATURES

- Top Mounted System
- Heated Cabinet Facia to prevent condensation
- Manual Defrost
- Castors/Legs
- Stainless Steel Interior
- Digital Display with Built-in Alarms
- Adjustable Shelves
- Hi/Lo Readout
- Static Refrigeration



-18°C to -22°C



356 L
505 L



650w x 700d x 1920h
800w x 750d x 1965h

+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

NHF SPARK SAFE FREEZER

NULINE
REFRIGERATION

MODEL	NHF400	NHF600
Gross Capacity	356 L	505 L
External Dimensions in mm (w/d/h including castors or legs)	650 x 700 x 1920	800 x 750 x 1965
Internal Dimensions in mm (w/d/h)	470 x 535 x 1550	590 x 585 x 1600
Packed Dimensions in mm (w/d/h including pallet)	750 x 800 x 2050	850 x 850 x 2115
Gross Weight – kg (packed weight)	105	121
Net Weight – kg	95	115
Voltage	240V	240V
Temperature Range	-18°C to -22°C	-18°C to -22°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R404a	R404a
Cooling System / Defrost	Static / Manual	Static / Manual
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	Stainless Steel	Stainless Steel
Door	Solid	Solid
Door Hinge	RH	RH
Door Handle	Lockable	Lockable
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual/Audible	Visual/Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Watts	780W	960W
Castors	Yes	Yes
Adjustable Shelves	5	5
Usable Shelf Area in mm (w/d)	450 x 415	570 x 515

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHFTS TOP MOUNTED SPARK SAFE FREEZER

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- Heated Cabinet Facia to prevent condensation
- Manual Defrost
- Static Refrigeration System
- Castors/Legs
- Stainless Steel Interior
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	-18°C to -22°C
	350 L 570L
	650w x 620d x 1980h 770w x 750d x 1965h



+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



NHFTS TOP MOUNTED SPARK SAFE FREEZER

NULINE
REFRIGERATION

MODEL	NHFTS400	NHFTS600
Gross Capacity	350 L	570 L
External Dimensions in mm (w/d/h including castors or legs)	650 x 620 x 1980	770 x 750 x 1965
Internal Dimensions in mm (w/d/h)	470 x 535 x 1405	670 x 600 x 1500
Packed Dimensions in mm (w/d/h including pallet)	750 x 850 x 2130	820 x 800 x 2130
Gross Weight – kg (packed weight)	102	121
Net Weight – kg	95	115
Voltage	240V	240V
Temperature Range	-18°C to -22°C	-18°C to -22°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R404a	R404a
Cooling System / Defrost	Static	Static
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	Stainless Steel	Stainless Steel
Door	Solid	Solid
Door hinge	RH	RH
Door Handle	Lockable	Lockable
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Watts	720W	960W
Castors	Yes	Yes
Adjustable Shelves	5	5
Usable Shelf Area in mm (w/d)	450 x 515	570 x 515

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHRiT REFRIGERATOR INCUBATOR

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- Five (5) rows of PVC Coated Shelves behind each door
- Interior Lighting LED
- Castors
- Automatic Water Disposal
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	10°C to 40°C
	350 L 590 L
	600w x 620d x 1980h 770w x 750d x 2030h



+61 3 9562 3355
info@nulinerefrigeration.com.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

Distributor

EVOCARE AUSTRALIA PTY LIMITED

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: sales@evocare.com.au

workshop@evocare.com.au

warehouse@evocare.com.au

accounts@evocare.com.au



Global-Mark.com.au®

NHRiT REFRIGERATOR INCUBATOR



MODEL	NHRiT400	NHRiT600
Gross Capacity	350 L	590 L
External Dimensions in mm (w/d/h including castors or legs)	600 x 620 x 1980	770 x 750 x 2030
Internal Dimensions in mm (w/d/h)	440 x 570 x 1435	670 x 600 x 1500
Packed dimensions in mm (w/d/h including pallet)	650 x 570 x 2130	820 x 800 x 2180
Gross Weight – kg (packed weight)	102	121
Net Weight – kg	95	115
Voltage	240V	240V
Temperature Range	10°C to 40°C	10°C to 40°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Temperature Fluctuation	-/+ 1.5°C	-/+ 1.5°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	White Colourbond	White Colourbond
Door	Glass / Solid	Glass / Solid
Door Hinge	RH	RH
Door Handle	Lockable	Lockable
Type of Controller	Digital / Microprocessor	Digital / Microprocessor
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirements	10amp GPO	10amp GPO
Castors	Yes	Yes
Adjustable Shelves	5	5
Usable Shelf Area in mm (w/d)	480 x 450	650 x 580
Light	LED	LED

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NHRiT REFRIGERATOR INCUBATOR

The logo for Nuline Refrigeration is an oval shape with a blue gradient. The word "NULINE" is written in large, white, bold, sans-serif capital letters. Below it, the word "REFRIGERATION" is written in smaller, white, sans-serif capital letters.

NULINE
REFRIGERATION

Since 1985, Nuline Refrigeration has been manufacturing refrigerators and freezer cabinets for the Australian market. Our specialised range of biomedical cabinets are used extensively across the hospitals, medical centres, pharmacies and laboratories.

Focusing on customer needs, we manufacture, import and customise the biomedical cabinets from a range of selected global suppliers. Our factory is based in Melbourne, Australia and we are proudly 100% Australian owned business.

Each of our manufactured cabinets are custom built based on customer orders by our craftsmen right here in Melbourne.

We have extensive capability to design, engineer and build a range of refrigerated cabinets for you. Our standard product range includes, fridges, freezers (up to -40°C), blanket warmer, mortuary refrigerators and refrigerated incubators.

