

# NLMB1006 PREMIUM QUALITY PHARMACY AND LABORATORY REFRIGERATOR

**NULINE**  
REFRIGERATION

This amazing premium quality pharmacy and laboratory refrigerator, comes complete with all the standard features plus almost every other feature you could want in a pharmacy and laboratory refrigerator.



Some stand out features include, heated glass doors to prevent condensation in high humidity areas and an easy to use, built in data logger.

This refrigerator provides an even temperature throughout by its fan forced system.

## FEATURES

- Digital Display with Built in Alarms
- Hi/Lo Readout
- Door Ajar Alarms
- Built in Data Logger
- Port Entry
- Remote Alarm Contacts
- Heated Glass Doors



	2°C to 8°C
	1006 L
	1220w x 872d x 1865h

+61 3 9562 3355  
info@nuline.au  
7 Longford Court, Springvale VIC 3171  
[www.nulinerefrigeration.com.au](http://www.nulinerefrigeration.com.au)



# NLMB1006 PREMIUM QUALITY PHARMACY AND LABORATORY REFRIGERATOR



MODEL	NLMB1006
Gross Capacity	1006 L
External Dimensions in mm (w/d/h including castors)	1220 x 872 x 1865
Internal Dimensions in mm (w/d/h)	1100 x 684 x 1325
Packed Dimensions in mm (w/d/h including pallet)	1335 x 945 x 2000
Gross Weight – kg (packed weight)	237
Net Weight – kg	189
Voltage	240V 50Hz
Temperature Range	2°C to 8°C
Ambient Temperature Range	10°C to 32°C
Temperature Fluctuation	-/+ 1.5°C
Refrigerant	R600
Cooling System / Defrost	Fan Forced / Automatic
Exterior Cabinet Finish	Enamelled Steel
Inner Liner Material	Enamelled Steel
Door	Heated Glass / Self-Closing
Door Hinge	LH / RH
Door Handle	Yes
Type of Controller	Microprocessor
Temperature Display	External / Digital
Data Logger	Built-in
Door Ajar Alarms	Visual / Audible
High and Low Readout	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Yes Optional
Clip on Data Strip	Yes
Port Entry	Yes (25mm)
Battery Back-up for Controller	Yes (lasts approx. 8 hours)
Power Requirement	10amp GPO
Castors	Yes
Adjustable Shelves	10
Usable Shelf Area in mm (w/d)	510 x 620
Light	Yes
Noise	53 dB(A)



Nuline Refrigeration reserves the right to alter the specifications without prior notice.


# NLMB LABORATORY AND MEDICAL

**NULINE**  
REFRIGERATION

## FEATURES

- Bottom Mounted System
- E-glass and Heated Cabinet Facia to prevent condensation up to 80% R.H.
- Lockable Handle
- Automatic Water Disposal
- Double Glazed Doors
- Interior Light LED
- Digital Display with Built-in Alarm
- Hi/Lo Readout



	2°C to 8°C
	820 L 1171 L
	1200w x 700d x 2080h 1880w x 700d x 2080h



+61 3 9562 3355  
[info@nulinerefrigeration.com.au](mailto:info@nulinerefrigeration.com.au)  
7 Longford Court, Springvale VIC 3171  
[www.nulinerefrigeration.com.au](http://www.nulinerefrigeration.com.au)

Distributor

**EVOCARE AUSTRALIA PTY LIMITED**

A.B.N. 98 078 566 604

Trading as **EVOCARE** and **L&M EQUIPMENT**

P.O. Box 1144, Stafford Qld. 4053

Ph: 07 3355 8000 Fax: 07 3355 5043

Website: <http://www.evocare.com.au>

Email: [sales@evocare.com.au](mailto:sales@evocare.com.au)

[workshop@evocare.com.au](mailto:workshop@evocare.com.au)

[warehouse@evocare.com.au](mailto:warehouse@evocare.com.au)

[accounts@evocare.com.au](mailto:accounts@evocare.com.au)



Global-Mark.com.au®

MODEL	NLMB2	NLMB3
Gross Capacity	820 L	1171 L
External Dimensions in mm (w/d/h including castors or legs)	1200 x 700 x 2080	1880 x 700 x 2080
Internal Dimensions in mm (w/d/h)	1100 x 600 x 1450	1780 x 600 x 1450
Packed Dimensions in mm (w/d/h including pallet)	1250 x 750 x 2230	1820 x 750 x 2230
Gross Weight – kg (packed weight)	137	190
Net Weight – kg	125	175
Voltage	240V	240V
Temperature Range	2°C to 8°C	2°C to 8°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced
Exterior Cabinet Finish	White Colourbond	White Colourbond
Inner Liner Material	White Colourbond	White Colourbond
Door	Solid / Glass E-Glass	Solid / Glass E-Glass
Door Hinge	LH / RH	LH / RH / RH
Door Handle	Lockable	Lockable
Type of Controller	Digital	Digital
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back-Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Castors	Yes	Yes
Adjustable Shelves	4	12
Usable Shelf Area in mm (w/d)	1080 x 530	585 x 530
Light	LED	LED