





"The Pelican hoist complies with the Disability 'Access to Premises' under the Building Code of Australia 2010 standard, which falls under the Disability Discrimination Act of 1992."

— Anthony Leuzzi of Morris Goding Accessibility Consulting

The Pelican Pool and Spa Hoist is designed and manufactured in Australia from Stainless Steel and powder coated to the clients specifications.


The Pelican has been manufactured to Australian Standards specifically AS 3581 and complies with Building Code of Australia legislation 'Disability (Access to Premises – buildings) Standards 2010.

The Pelican comes in two different sizes with lifting capacities of 150kg and 200kg.

The seating options include a floating sling, solid plastic seat or a wet area wheelchair which can be lowered into the water.

Standard arm length is 1500mm. Alternate arm lengths can be manufactured.

A Pelican Measuring Guide must be completed before manufacture commences to ensure the hoist has adequate reach.









SPECIFICATIONS

HOIST

Safe Working Load 150kg & 200kg

Drive Linak Linear System

Hoist manufacture Stainless steel

6 x threaded anchors **Anchoring**

Chemically set into concrete

Linak - 24v re-chargeable battery Power

Hand Control Linak - Push Button

From in ground pool level to above ground 1200mm high spa Lifting Range

Can be modified to suit client's needs

Power Rotation Manual rotation as standard with power rotation available as an option

Overall Weight Standard hoist from 60kg dependent on model

Finish Powder coated to colour of choice from a range of Dulux colours

SEAT

Pelican Wet Area Wheelchair

- Stainless steel strengthening frame and lifting straps
- SWL 150kg
- Bariatric size SWL 200kg
- PVC frame
- Mesh fabric open weave for seat and back allowing water drainage and airflow
- Lap belt
- Dual foot-plates
- Self-propelling wheels
- Optional harness for chest support and child adapter can be inserted for torso control

Floating Sling Padded PVC SWL 150kg / SWL 200kg

Solid Plastic Chair Includes lap belt, SWL 150kg / SWL 200kg. Twin arm construction required.


Platform Construction Stainless steel and powder coated to a colour of your choice. Size 1550 mm x 920mm. SWL 200kg. Twin arm construction required.

Earthing: As per AS3000 of the wiring rules standards - "In certain circumstances" it may be necessary to have all conductive metal objects equally potentially bonded (earthed), this includes Pool Hoists.


The pool hoist must be earthed by a qualified electrician.



"This will be a great boost to my wife's health and lifestyle" - Mr Lauritz, purchased January 2017







ANCHOR POINTS



FLOATING SLING



SOLID SEAT TWIN ARM



PELICAN WHEELCHAIR



MEASUREMENT GUIDE

GRATE

Α

DO YOU HAVE THE MINIMUM CONCRETE WIDTH AND THICKNESS TO MOUNT THE HOIST ON POOL DECK? Y | N

